

Mobil Super 4T 15W-40

High Performance Four-Stroke Motorcycle Engine Oil

Product Description

Mobil Super 4T 15W-40 is a high performance conventional four-stroke motorcycle engine oil primarily intended for general use in all types of four-stroke motorcycles and engines.

Features and Benefits

Mobil Super 4T 15W-40 combines highly refined, quality mineral oils and an advanced additive system to provide good engine cleanliness, good wear protection and corrosion protection. Key features and benefits include:

Features	Advantages and Potential Benefits
Good wear protection	Extends engine life
Thermal and oxidation stability	Keeps engines clean for smoother operation
Good corrosion protection	Protects critical engine components
Broad viscosity range	Year round engine protection and performance

Applications

Mobil Super 4T 15W-40 is recommended for lubrication of all four-stroke motorcycle engines where an API SG and JASO MA level performance is recommended.

Specifications and Approvals

Mobil Super 4T meets or exceeds the following industry specifications:	15W-40
API	SG
JASO MA	MA

Typical Properties

Mobil Super 4T	15W-40
SAE Grade	15W-40
Viscosity, ASTM D 445	
cSt @ 40°C	107
cSt @ 100°C	14.4
Viscosity Index, ASTM D 2270	141
Sulfated Ash, wt%, ASTM D 874	0.91
Pour Point, °C, ASTM D 97	-24
Flash Point, °C, ASTM D 92	



Mobil Super 4T

15W-40

Density @15°C, kg/l, ASTM D 4052

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contact office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design and Super 4T are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.